



US006797187B1

(12) **United States Patent**  
Galambos et al.

(10) Patent No.: **US 6,797,187 B1**  
(45) Date of Patent: **Sep. 28, 2004**

(54) **SURFACE-MICROMACHINED MICROFLUIDIC DEVICES**

(75) Inventors: **Paul C. Galambos**, Albuquerque, NM (US); **Murat Okandan**, Albuquerque, NM (US); **Stephen Montague**, Albuquerque, NM (US); **James H. Smith**, Redmond, WA (US); **Phillip H. Paul**, Livermore, CA (US); **Thomas W. Krygowski**, Cutchland Manor, NY (US); **James J. Allen**, Albuquerque, NM (US); **Christopher A. Nichols**, Hauppauge, NY (US); **Jerome F. Jakubczak II**, Rio Rancho, NM (US)

(73) Assignee: **Sandia Corporation**, Albuquerque, NM (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 84 days.

(21) Appl. No.: **10/351,135**

(22) Filed: **Jan. 24, 2003**

**Related U.S. Application Data**

(62) Division of application No. 09/712,634, filed on Nov. 13, 2000, now Pat. No. 6,537,437.

(51) **Int. Cl.** <sup>7</sup> ..... **B01D 67/00**

(52) **U.S. Cl.** ..... **216/2; 216/27; 216/41; 216/80; 216/97**

(58) **Field of Search** ..... **216/2, 16, 27, 216/41, 80, 97; 438/21, 49-54; 219/630**

(56) **References Cited****U.S. PATENT DOCUMENTS**

- |             |         |         |       |         |
|-------------|---------|---------|-------|---------|
| 5,501,893 A | 3/1996  | Laermer | ..... | 428/161 |
| 5,582,701 A | 12/1996 | Geis    | ..... | 204/451 |
| 5,591,139 A | 1/1997  | Lin     | ..... | 604/264 |
| 5,804,084 A | 9/1998  | Nasby   | ..... | 216/2   |
| 5,824,204 A | 10/1998 | Jerman  | ..... | 204/601 |

5,985,119 A	11/1999	Zanzucchi	.....	204/450
6,013,164 A	1/2000	Paul	.....	204/450
6,019,882 A	2/2000	Paul	.....	204/450

(List continued on next page.)

**OTHER PUBLICATIONS**

L. Bousse and S. Mostarshed, "The Zeta Potential of Silicon Nitride," *Journal of Electroanalytical Chemistry*, vol. 302, pp. 269-274 (1991).

P.H. Paul, D.W. Arnold and D.J. Rakestraw, "Electrokinetic Generation of High Pressures Using Porous Microstructures," *Proceedings of Micro Total Analysis Systems (μTAS) '98*; pp. 49-52 (Oct. 1998).

P. Galambos, B. Eaton, J. Smith, R. Shul, C.W. Gober, J. Sniegowski, S. Miller and D. Gutierrez, "Surface Micromachined Microfluidics: Design, Fabrication, Packaging, and Characterization," Paper presented at the 1999 International Mechanical Engineering Congress and Exposition, Nashville, TN, Nov. 14-19, 1999.

A. V. Lernoff and A.P. Lee, "An AC Magnetohydrodynamic Micropump," *Sensors and Actuators B*, vol. 63, pp. 178-185 (2000).

*Primary Examiner*—Allan Olsen

(74) *Attorney, Agent, or Firm*—John P. Hohimer

(57) **ABSTRACT**

Microfluidic devices are disclosed which can be manufactured using surface-micromachining. These devices utilize an electroosmotic force or an electromagnetic field to generate a flow of a fluid in a microchannel that is lined, at least in part, with silicon nitride. Additional electrodes can be provided within or about the microchannel for separating particular constituents in the fluid during the flow based on charge state or magnetic moment. The fluid can also be pressurized in the channel. The present invention has many different applications including electrokinetic pumping, chemical and biochemical analysis (e.g. based on electrophoresis or chromatography), conducting chemical reactions on a microscopic scale, and forming hydraulic actuators.

**6 Claims, 12 Drawing Sheets**

